

Zp soby p ipojení | Anschlussmöglichkeiten | Connection methods

strana | Seite | page # 2

A = 46mm (+/- 1%) | C = 64, 101, 139, 177, 215mm | D = (A x n° el.)+25mm | E = 120 - 145mm | I = B-70mm
B = 220, 260, 300, 350, 400, 450, 500, 550, 600, 750, 900, 1000, 1100, 1200,, 1500, 1800, 2000, 2200, 2500, 2800, 3000mm

Rozm ry | Abmessungen | Sizes

*) všechny údaje v mm | alle Angaben in mm | all dimensions in mm




+30% ostatní barvy | andere Farben | other colours
+0% RAL 9010 bílá | Weiss | white

Barva | Farbe | Colour




Horizontální | Horizontal | Horizontal version



Temp. +2°C ~ +45°C | Hum. 20%-70%
Práškový lak | Pulverlack | powder-coating

Povrch | Oberfläche | Surface




El. verze | Variante | version



Ocel | Stahl | steel

Materiál | Material | Material



max. 70 lánk | Glieder | elements

Na míru | Auf Mass | Made to measure



max. 90° C | max. 10 bar

Požadavky | Anforderungen | requirements



+2 týdny speciál | Wochen Massarbeit | for specials
4 Týdny | Wochen | weeks

Dodací termín | Lieferzeiten | Delivery times

CONN-V01		CONN-V08	
CONN-V02		CONN-V09	
CONN-V03		CONN-V10	
CONN-V04		CONN-V11	
CONN-V05		CONN-V12	
CONN-V06		CONN-V13	
CONN-V07		CONN-V13m	

Legenda | Icons | Symbole

- Vstup - Inlet - Vorlauf
- Výstup - Outlet - Rücklauf
- Výpus - Drain - Entleerung
- Odvzduš ení - Air-vent - Entlüftung

Legenda | Icons | Symbole

- 100% t sná p epážka - seal diaphragm - dichter Trennwand
- Propustná p epážka - diaphragm - norlamer Trennwand
- standard | standard connection | Standardanschluss
- p íplatek | surcharge | Aufpreis